


This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		BECAUSE OF DIFFERENT ENGRAVINGS CREATED -18 RECEIVER TO REPLACE -07 ON TOOL RBW6205G19432-3G. ADDED ENGRAVING NOTES TO -07 & -18. ADDED -3G TO ALL PART NUMBERS. TO -27 ADDED REF. DIMENSIONS. ON -3 & -17 DRAW BOLTS CHANGED ENGRAVINGS FROM T/N, S/N, ECT. TO T/N ONLY.	9/21/2009	WP	RW
2	16-0031	UPDATED TO NEW STANDARDS. -1, -5, -7 CH'D FINISH WAS YELLOW ZINC PLATE IS ZINC PLATE ASTM B633 TYPE I SC2. --1 ADDED MAT'L OPTION 4142 Q&T. CH'D FINISH WAS YELLOW ZINC PLATE IS ZINC PLATE ASTM B633 TYPE I SC2. CH'D DIMS WAS 2.950 IS 2.95, WAS .946 IS .95, WAS .120 IS .12, WAS 7.276 IS 7.28, WAS 1.572 IS Ø1.57. -3 CH'D DIMS WAS 3X .015 X 45° IS 3X .02 X 45°. WAS 1.970 IS 1.97, WAS .215 IS .22, WAS 1.256 IS 1.26. ADDED ENGRAVE NOTE. -5 CH'D DIMS WAS 4X .015 X 45° IS 4X .02 X 45°, WAS 2.950 IS 2.95. -7 CH'D DIM WAS .276 IS .28. -9 CH'D DIM WAS .882 HEX IS 3X .88.	2/11/2016	DPD	JAG






NOTES:  
1. ALSO SOLD WITH KIT RBW6205G19232-3G.  
2. REF. AGUSTA T/N: 3G6205G19432.

<b>DART AEROSPACE</b>	
TITLE M/R SCISSOR BUSHING INSTALL TOOL	
DWG NO. RBW6205G19432-3G	REV 2
MAT'L REPT TREAT FINISH	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX ± .01 ANGLES ± 5° .X ± .1 SURFACES = 125°
SPEC	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
DRAWN BY: CLOUGH	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
CHECKED: CLOUGH	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
OPPS APPR: ANDERSON	USED ON MODEL
QA APPR: LINDSAY	AGUSTA AW139
APPROVED: GILBERT	
SCALE 1:2	DATE 7/8/2009
SHEET 1 OF 6	

ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
			-1	1	DRAW BOLT	4140/4142 Q & T		2
			-3	1	RECEIVER	6061		3
			-5	1	SLEEVE	1018/1020 CR		4
			-7	1	WASHER	1018/1020 CR		5
			-9	1	TALL NUT	BRONZE ALLOY 642		6
		B/O	-11	1	THRUST BEARING	STEEL	Ø.562 I.D. X Ø1.000 O.D. X .0781 (APPLIED #NTA-916)	1
		B/O	-13	2	THRUST WASHER	STEEL	Ø.562 I.D. X Ø1.000 X .031 (APPLIED #TRA-916)	1

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
2	16-0031	-1 ADDED MAT'L OPTION 4142 Q&T. CH'D FINISH WAS YELLOW ZINC PLATE IS ZINC PLATE ASTM B633 TYPE I SC2. CH'D DIMS WAS 2.95 IS 2.95, WAS .946 IS .95, WAS .120 IS .12, WAS 7.276 IS 7.28, WAS 1.572 IS Ø1.57.	2/11/2016	DPD	JAG






(-1)  
DRAW BOLT

<b>DART AEROSPACE</b>	
TITLE <b>M/R SCISSOR BUSHING INSTALL TOOL</b>	
DWG NO. <b>RBW6205G19432-3G-1</b>	REV <b>2</b>
MAT'L 4140/4142 Q & T HEAT TREAT FINISH ZINC PLATE SPEC ASTM B633 TYPE I SC 2	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX ± .01 ANGLES ± 5° .X ± .1 SURFACES = 125° ✓	
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
DRAWN BY: <b>CLOUGH</b>	USED ON MODEL
CHECKED: <b>CLOUGH</b>	AGUSTA AW139
OPPS APPR: <b>ANDERSON</b>	
QA APPR: <b>LINDSAY</b>	
APPROVED: <b>GILBERT</b>	
SCALE 1:2	DATE 7/8/2009
SHEET 2 OF 6	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
2	16-0031	-3 CH'D DIMS WAS 3X .015 X 45° IS 3X .02 X 45°, WAS 1.970 IS 1.97, WAS .215 IS .22, WAS 1.256 IS 1.26. ADDED ENGRAVE NOTE.	2/11/2016	DPD	JAG






SECTION A-A

(-3)  
RECEIVER

<b>DART AEROSPACE</b>	
TITLE <b>M/R SCISSOR BUSHING INSTALL TOOL</b>	
DWG NO. <b>RBW6205G19432-3G-3</b>	REV <b>2</b>
MAT'L 6061	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH CLEAR ANODIZE	.XXX ± .005 FRACTIONS ± 1/8
SPEC MIL-A-8625, TYPE II, CLASS I	.XX ± .01 ANGLES ±.5°
DRAWN BY: CLOUGH	.X ± .1 SURFACES = 125✓
CHECKED: CLOUGH	1. BREAK ALL SHARP EDGES
OPPS APPR: ANDERSON	.015 x 45° OR .015R
QA APPR: LINDSAY	2. DIMENSIONAL LIMITS APPLY
APPROVED: GILBERT	AFTER PLATING
SCALE 1:1	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
DATE 7/8/2009	USED ON MODEL
SHEET 3 OF 6	AGUSTA AW139

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
2	16-0031	-5 CH'D FINISH WAS YELLOW ZINC PLATE IS ZINC PLATE ASTM B633 TYPE I SC2. CH'D DIMS WAS 4X .015 X 45° IS 4X .02 X 45°, WAS 2.950 IS 2.95.	2/11/2016	DPD	JAG






(-5)  
SLEEVE

<b>DART AEROSPACE</b>	
TITLE M/R SCISSOR BUSHING INSTALL TOOL	
DWG NO. RBW6205G19432-3G-5	REV 2
MAT'L 1018/1020 CR	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
HEAT TREAT	.XXX ± .005 FRACTIONS ± 1/8
FINISH ZINC PLATE	.XX ± .01 ANGLES ± 5°
SPEC ASTM B633 TYPE I SC 2	.X ± .1 SURFACES = 125° ✓
DRAWN BY: CLOUGH	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
CHECKED: CLOUGH	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
OPPS APPR: ANDERSON	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
QA APPR: LINDSAY	USED ON MODEL
APPROVED: GILBERT	AGUSTA AW139
SCALE 1:1	DATE 7/8/2009
SHEET 4 OF 6	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
2	16-0031	-7 CH'D FINISH WAS YELLOW ZINC PLATE IS ZINC PLATE ASTM B633 TYPE I SC2. CH'D DIM WAS .276 IS .28.	2/11/2016	DPD	JAG






(-7)

WASHER

<b>DART</b> AEROSPACE	
TITLE M/R SCISSOR BUSHING INSTALL TOOL	
DWG NO. RBW6205G19432-3G-7	REV 2
MAT'L 1018/1020 CR	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH ZINC PLATE	.XXX ± .005 FRACTIONS ± 1/8
SPEC ASTM B633 TYPE I SC 2	.XX ± .01 ANGLES ± 5°
DRAWN BY: CLOUGH	.X ± .1 SURFACES = 125
CHECKED: CLOUGH	1. BREAK ALL SHARP EDGES
OPPS APPR: ANDERSON	.015 x 45° OR .015R
QA APPR: LINDSAY	2. DIMENSIONAL LIMITS APPLY
APPROVED: GILBERT	AFTER PLATING
SCALE 1:1	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
DATE 7/8/2009	USED ON MODEL
SHEET 5 OF 6	AGUSTA AW139

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
2	16-0031	-9 CH'D DIM WAS .882 HEX IS 3X .88.	2/11/2016	DPD	JAG



(-9)

TALL NUT

<b>DART</b> AEROSPACE	
TITLE M/R SCISSOR BUSHING INSTALL TOOL	
DWG NO. RBW6205G19432-3G-9	REV 2
MAT'L BRONZE ALLOY 642	UNLESS OTHERWISE SPECIFIED
HEAT TREAT FINISH	DIMENSIONS ARE IN INCHES
SPEC	.XXX ± .005 FRACTIONS ± 1/8
DRAWN BY: CLOUGH	.XX ± .01 ANGLES ± 5°
CHECKED: CLOUGH	.X ± .1 SURFACES = 125°
OPPS APPR: ANDERSON	1. BREAK ALL SHARP EDGES
QA APPR: LINDSAY	.015 x 45° OR .015R
APPROVED: GILBERT	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
SCALE 2:1	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
DATE 7/8/2009	USED ON MODEL
SHEET 6 OF 6	AGUSTA AW139